

## BOX | built-in part for thermostatic 3-way shower/bath mixer

---

### Finish:

The built-in part for thermostatic 3-way shower/bath mixer is equipped with a brass body, high-quality thermostatic cartridge, switches, and valves with filters. Its advantages include easy installation and a minimal installation depth of only 7 cm. The BOX is designed to be paired with exposed elements: Y1238/KROWM, Y1238/KROCR, Y1238/KRONI, Y1238/KROGR, Y1238/KROCPB, Y1238/KROCP, Y1238/KROBSB, Y1238/KROGL, Y1238/KROGLB, Y1238/KROBL, FR7138ROCR.



Certificates: Polish Hygienic Certificate PZH

## Technologies

---



The mixer is equipped with the highest quality thermostatic cartridge incorporating a 38°C lock. The cartridge protects against sudden temperature changes and guarantees long term product performance.

## Flow characteristics

---

- water flow at 3 bar: 22/27 l/min
- hot water supply: max. 90 °C
- working pressure 1-10 bar

## Specification

---

- minimum wall depth: 7 cm
- two 3/4" inlets (hot and cold water)
- three 1/2" mixed water outlets
- with filters and non-return valves
- hot water lock at 38°C
- complementary product to: Y1238/KROWM, Y1238/KROCR, Y1238/KRONI, Y1238/KROGR, Y1238/KROCPB, Y1238/KROCP, Y1238/KROBSB, Y1238/KROGL, Y1238/KROGLB, Y1238/KROBL, FR7138ROCR

