

SLIMLINE | shower head with arm, ø25 cm

Finish: brushed copper (CPB)

Shower head internally lined with rubber offering additional protection against damage.

Certificates: Polish Declaration of Performance (B marking), Polish Hygienic Certificate PZH



Technologies



Developed to minimise environmental footprint, the ECO WATER technology reduces water consumption by approx. 30% without compromising on the overall product experience.



Thanks to the AIR WATER technology, the water is soft and pleasant to the touch, enhancing the overall showering experience.



The shower head is made using the ANTI-SCALE technology. It incorporates a silicone insert that prevents internal water stagnation. Occasional tilting of the shower head, so that any stagnant water could flow out through the nozzles, guarantees long term product performance.



The EASY CLEAN nozzles allow the user to easily remove any limescale build up by simply wiping their silicone surface.



The product is coated using the advanced PVD technology which guarantees the highest possible durability and facilitates cleaning.



The product is made of high quality A-grade brass.

Flow characteristics

- water flow at 3 bar: 11 l/min
- working pressure 1-5 bar
- noise class: II

Specification

- brass
- shower head, 1-function, dimensions: $\varnothing 25$ cm
- reach from the wall: 41 cm
- flow rate: 11 l/min.

Product care

How to take care of a shower head?

Remember to regularly wipe the silicone nozzles with your hand to remove any limescale deposits that might be forming on their surface. Avoid using harsh cleaning agents that may damage the nozzles and the surface of the shower head.

The shower head should be angled after each use to allow the remaining water to flow out. This is the easiest yet necessary way to reduce the build-up of limescale from the water inside the shower head. Tilting the shower head additionally reduces the risk of the product becoming prone to leaking, allowing the product to serve its purpose reliably for an extended time.

