SLIMLINE | shower head with arm, ø25 cm

Finish: brushed nickel (NI)

Shower head internally lined with rubber offering additional protection against damage.

Nickel is an industrial finishing in a silvery colour, with a satin, brushed surface. The product is coated using the advanced PVD technology.

Certificates: Polish Declaration of Performance (B marking), Polish Hygienic Certificate PZH



OMNIRES

Technologies



Developed to minimise environmental footprint, the ECO WATER technology reduces water consumption by approx. 30% without compromising on the overall product experience.

The shower head is made using the ANTI-SCALE

prevents internal water stagnation. Occasional tilting

of the shower head, so that any stagnant water could flow out through the nozzles, guarantees long term

technology. It incorporates a silicone insert that



The EASY CLEAN nozzles allow the user to easily remove any limescale build up by simply wiping their silicone surface.

showring experience.



The product is made of high quality A-grade brass.

Thanks to the AIR WATER technology, the water is

soft and pleasant to the touch, enhancing the overall



The product is coated using the advanced PVD technology which guarantees the highest possible durability and facilitates cleaning.

Flow characteristics

• water flow at 3 bar: 11 l/min

product performance.

- working pressure 1-5 bar
- noise class: II

Specification

- brass
- shower head, 1-function, dimensions: ø25 cm
- reach from the wall: 41 cm
- flow rate: 11 l/min.

Product care

How to take care of
>a shower head?

Remember to regularly wipe the silicone nozzles with your hand to remove any limescale deposits that might be forming on their surface. Avoid using harsh cleaning agents that may damage the nozzles and the surface of the shower head.

The shower head should be angled after each use to allow the remaining water to flow out. This is the easiest yet necessary way to reduce the build-up of limescale from the water inside the shower head. Tilting the shower head additionally reduces the risk of the product becoming prone to leaking, allowing the product to serve its purpose reliably for an extended time.

