OMNIRES

BRONX | sliding shower door, 140 cm

Finish: polished chrome / transparent glass (CRTR)

For cleaning purposes, the glass door may be easily clipped off the profiles.

Certificates: European Declaration of Performance (CE marking)



Technologies



The CLIP-OFF rollers allow the user to easily remove the glass panels from the frame, in order to thoroughly clean all surfaces.



Thanks to the DUAL MOUNT system, shower enclosure may be installed on either side.

Flow characteristics

• working pressure 1-5 bar

Specification

width: 140 cmentrance: 59.7 cmheight: 185 cm

• tempered safety glass, thickness: 5 mm

• aluminium profiles, profile adjustment -2/+2 cm

• chrome-plated handle

Product care

What is the most effective way to clean a shower enclosure?

The glass walls of the shower enclosure should be cleaned regularly, preferably after each use, using a soft cloth (for example, a microfibre cloth) and a solution of water with a mild cleaning agent with a natural composition. After cleaning the enclosure, rinse the inner glass surface thoroughly and remove any remaining water with a rubber squeegee or soft cloth. You can clean the outer side of the glass walls using a mirror or glass cleaner. It is important to avoid using rough, abrasive materials and caustic or bleaching substances to prevent damaging the surface of the glass.

To tackle stubborn dirt or limescale deposits, you can use cleaning agents dedicated to shower enclosures. It is recommended to lubricate hinges, joints, guide tracks and rollers at least once a year using technical lubricant or silicone grease to ensure their smooth operation.

