

ECO FLUSH SET | STRONGFRAME concealed frame with ECO flushing for a wall-mounted toilet + MINIMAL flush plate

Finish: matt black (BLM)

The set comprising the concealed OMNIRES STRONGFRAME system and the OMNIRES MINIMAL flush plate was designed with contemporary bathrooms in mind, where aesthetics and functionality go hand in hand. The concealed cistern, made from a single element, guarantees complete leak-tightness, and the insulation used limits moisture condensation, dampens noise, and reduces vibrations, providing a high level of comfort and discretion during use.

Thanks to precise adjustment options, the frame allows to save water – water use is from 2 litres on a small flush and 3 litres on a large flush – without loss of functional efficiency.

The OMNIRES MINIMAL dual flush plate was designed for simple and intuitive installation. Its slim design seamlessly integrates into the wall, while the round shape of the buttons and perfectly balanced proportions offer exceptional comfort in daily use. Intuitive markings make it easy to select the right flush volume, tailored to individual needs, ensuring both water savings and greater comfort with every use.

The flush plate comes in a matt black finish – a striking shade with a deep tone and a perfectly smooth, satin surface.



Technologies



Thanks to the innovative flushing technology, the water consumption is minimised.

Specification

- STRONGFRAME concealed frame for drywall installation; height: 112 cm, width: 51 cm, frame depth: 12.5 cm, installation depth: 12.5–25 cm
- can be installed in front of a wall or inside a stud wall
- for a wall-mounted toilet bowl with a fixing bolt distance of 180 mm or 230 mm
- adjustable anchor feet with a locking system and a range of 0–20 cm
- sliding rail holder for the waste connector can be set to eight positions between 0 and 9.3 cm
- G 1/2 water connection with integrated G 3/8 angle valve
- water connection can either be at the back or at the top
- can be connected to external ventilation
- sound insulation mat included in the set
- concealed system with a 9-litre cistern capacity and polystyrene insulation to prevent condensation on the tank surface and to dampen vibrations transmitted from the tank to the building structure
- flushing volume factory settings: 2 litres / 4 litres
- flushing water can be adjusted using the flushing valve: small flush 2–4 litres / large flush 3–6 litres
- recommended for toilet bowls with SILENT POWER™ technology
- dual flush plate MINIMAL made of ABS plastic; dimensions: 24.5 x 16.5 cm

