

## UNI | thermostatic shower system for exposed installation

---

Finish: matt black (BLM)

Certificates: Polish Declaration of Performance (B marking)



## Technologies

---



The mixer is equipped with the highest quality thermostatic cartridge incorporating a 38°C lock. The cartridge protects against sudden temperature changes and guarantees long term product performance.



The shower head is made using the ANTI-SCALE technology. It incorporates a silicone insert that prevents internal water stagnation. Occasional tilting of the shower head, so that any stagnant water could flow out through the nozzles, guarantees long term product performance.



The EASY CLEAN nozzles allow the user to easily remove any limescale from the shower head and the hand shower by simply wiping their silicone surface.



The mixer and the shower head are made of high quality A-grade brass.

## Flow characteristics

---

- water flow at 3 bar: 16 l/min
- hot water supply: max. 90 °C
- working pressure 1-10 bar

## Specification

---

- thermostatic shower mixer
- hot water lock at 38°C
- shower head, dimensions: 20 x 20 cm, reach from the wall: 43 cm
- hand shower (JIMJIM-RBL), 3-function, streams: rain, whip, mixed
- PVC-coated flexible shower hose (028BL), length: 150 cm
- shower head/hand shower stream switch embedded in the water knob
- adjustable height, minimum/maximum system height: 93 cm/133 cm

