

UNI | thermostatic shower system for exposed installation

Finish: polished chrome (CR)



Technologies



The mixer is equipped with the highest quality thermostatic cartridge incorporating a 38°C lock. The cartridge protects against sudden temperature changes and guarantees long term product performance.



The ULTRA SLIMLINE showerhead has been designed with environmental footprint in mind. Its ergonomic, subtle shape minimizes water flow and reduces the overall water consumption.



The shower head is made using the ANTI-SCALE technology. It incorporates a silicone insert that prevents internal water stagnation. Occasional tilting of the shower head, so that any stagnant water could flow out through the nozzles, guarantees long term product performance.



The EASY CLEAN nozzles allow the user to easily remove any limescale from the shower head and the hand shower by simply wiping their silicone surface.



The product's coating, made using advanced galvanization technology, is durable and easy to clean.



The mixer's body, the valve and the rosette are all made of high quality A-grade brass.



The shower head is made of high quality stainless steel.

Flow characteristics

- hot water supply: max. 90 °C
- water flow at 3 bar: 16 l/min
- working pressure 1-10 bar

Specification

- thermostatic shower mixer
- hot water lock at 38°C
- stainless steel shower head (WGU220CR), dimensions: 20 x 20 cm, reach from the wall: 43 cm
- hand shower (HUDSONX-RCR), 1-function
- stainless steel flexible shower hose, length: 150 cm
- shower head/hand shower stream switch embedded in the water knob
- adjustable height, minimum/maximum system height: 90 cm/130 cm

