

UNI | thermostatic shower system for exposed installation

Finish: polished chrome (CR)



Technologies



The mixer is equipped with the highest quality thermostatic cartridge incorporating a 38°C lock. The cartridge protects against sudden temperature changes and guarantees long term product performance.



The shower head is made using the ANTI-SCALE technology. It incorporates a silicone insert that prevents internal water stagnation. Occasional tilting of the shower head, so that any stagnant water could flow out through the nozzles, guarantees long term product performance.



The product's coating, made using advanced galvanization technology, is durable and easy to clean.



Developed to minimise environmental footprint, the ECO WATER technology reduces water consumption by approx. 30% without compromising on the overall product experience.



The EASY CLEAN nozzles allow the user to easily remove any limescale build up by simply wiping their silicone surface.



The mixer's body, the valve and the rosette are all made of high quality A-grade brass.

Flow characteristics

- hot water supply: max. 90 °C
- working pressure 1-10 bar

Specification

- thermostatic shower mixer
- hot water lock at 38°C
- stainless steel shower head (WGU220CR), dimensions: 20 x 20 cm, reach from the wall: 43 cm
- hand shower (JIMJIM-RCR), 3-function
- brass flexible shower hose, length: 150 cm
- shower head/hand shower stream switch embedded in the water knob
- adjustable height, minimum/maximum system height: 90 cm/130 cm

