

STRONGFRAME | concealed frame for a wall-mounted toilet, with ECO flushing

The OMNIRES STRONGFRAME concealed frame has been designed for modern bathroom spaces where both aesthetics and functionality matter. The concealed cistern, made from a single element, guarantees complete leak-tightness, and the insulation used limits moisture condensation, dampens noise, and reduces vibrations, providing a high level of comfort and discretion during use.

Thanks to precise adjustment options, the frame allows for water savings – water use is from 2 litres on a small flush and 4 litres on a large flush – without loss of functional efficiency.

The frame is fully compatible with OMNIRES MINIMAL and OMNIRES STEEL-R45 dual flush plates, enabling flexible aesthetic alignment while maintaining optimal performance and reliability.

Certificates: European Declaration of Performance (CE marking)



Technologies



For the sake of the environment, ECO flushing provides maximum efficiency while using less water – reducing consumption by up to 30%.

Specification

- STRONGFRAME concealed frame for drywall installation; height: 112 cm, width: 51 cm, frame depth: 12.5 cm, installation depth: 12.5–25 cm
- can be installed in front of a wall or inside a stud wall
- for a wall-mounted toilet bowl with a fixing bolt distance of 180 mm or 230 mm
- adjustable anchor feet with a locking system and a range of 0–20 cm
- sliding rail holder for the waste connector can be set to eight positions between 0 and 9.3 cm
- G 1/2 water connection with integrated G 3/8 angle valve
- water connection can either be at the back or at the top
- can be connected to external ventilation
- sound insulation mat included in the set
- concealed system with a 9-litre cistern capacity and polystyrene insulation to prevent condensation on the tank surface and to dampen vibrations transmitted from the tank to the building structure
- flushing volume factory settings: 2 litres / 4 litres
- flushing water can be adjusted using the flushing valve: small flush 2–4 litres / large flush 3–6 litres
- recommended for toilet bowls with SILENT POWER™ technology
- to be completed with the dual-flush plate MINIMAL or STEEL-R45 (linki do kolekcji)

